



## SKF BEARING rolling stock(Europe) G.m...



### Timken RCJO2 3/16 Flange-Mount Ball Bearing Units

Bearing No. RCJO2 3/16

RCJO2 3/16 Bearing 2D drawings and 3D CAD models

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	6.42
EAN	0087796061293
Product Group	M06110
Number of Mounting Holes	4
Mounting Method	Eccentric Collar
Housing Style	4 Bolt Square Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	GN203KRRB
Seals	Double Land Riding Rubber Contact
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch - Metric	Inch
Long Description	4 Bolt Square Flange Block; 2-3/16" Bore; 7.9" Bolt Circle; 5-5/8" Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 2-3/16" Length Thru Bore; Relubrica



## SKF BEARING rolling stock(Europe) G.m...

Other Features	Single Row   Heavy Duty   Wide Inner Race   With Set Screw
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	<a href="http://www.timken.com">http://www.timken.com</a>
Manufacturer Item Number	RCJO 2 3/16
Weight / LBS	14.15
D	2.188 Inch   55.575 Millimeter
d	2.188 Inch   55.575 Millimeter
Nominal Bolt Circle Diameter Round	7.9 Inch   200 Millimeter
Cartridge Pilot Depth	0 Inch   0 Millimeter
Bolt Spacing	5.625 Inch   142.88 Millimeter
Cartridge Pilot Diameter	0 Inch   0 Millimeter
Shaft Size d	2 3/16 in
Dimension D	6.063 in
Dimension E	3.020 in
Inside Ring Outside Diameter	3.228 in
Series	Medium-Duty
Weight	14.16 lb
Seal Type	Shroud Seal
Total Length L	177.80 mm
Housing Width A	2.311 in
Bolt Hole Spacing J	142.9 mm
Bolt Hole Size N	16 mm
Flange Thickness A1	17.5 mm



## SKF BEARING rolling stock(Europe) G.m...

Center of Bearing from Housing End A2	31.5 mm
Inside Ring Width B	=Bearings1_Inside Ring Width= mm
Bolt Size	M16
Center of Bearing from Bearing End S	31.5 mm
Static Load Rating	10000 lbf
Dynamic Load Rating	17800 lbf